Ultra High CRI 12V LED Strip for Commercial & Retail

Waveform Lighting's ultra high CRI LED strips are now available in 4000K and 5000K natural white options, perfect for commercial, retail, office and manufacturing environments.

With the industry's highest color rendering of 95 CRI and R9 > 85, color perception and visual appearance can be improved dramatically.


The back side of the LED strip includes pre-applied 3M VHB® double-sided tape, which provides a simple but extremely strong adhesive mounting method for all of your projects.

The LED strips are 16.4 feet (5.0 meters) in length, and are conveniently reeled for quick and easy application, and can be cut to length every 1-inch (25 mm) with just a pair of scissors.

FEATURES

- Available in both 4000K (natural white) or 5000K (bright white)
- 95+ CRI and R9 > 85
- 450 lumens per foot (1500 lumens per meter)
- 4 oz copper circuitry for reduced voltage drop
- For indoor use only





Download full photometric reports at https://www.waveformlighting.com/photometrics

ELECTRICAL SPECIFICATIONS

Input type:	Constant Voltage	
Input voltage:	12V DC	
Current draw per ft:	450 mA @ 12V DC	
Current draw per reel:	7.5 A @ 12V DC	
Power draw per ft:	5.5 W @ 12V DC	
Power draw per reel:	90 W @ 12V DC	
Max run:	16.4 ft (5 meters)	

MECHANICAL SPECIFICATIONS

Length:	16.43 ft (5008 mm)
Width:	0.394 in (10 mm)
Height:	0.067 in (1.7 mm)
LED spacing (OC):	0.327 in (8.3 mm)
Cut-line spacing:	0.984 in (25 mm)
PCB copper thickness:	4 oz
Wire leads (both ends):	16 AWG 13 78 in (350 mm)


POWER SUPPLY SELECTION

Compatible with Waveform Lighting PN 3091 or third-party 12V DC constant voltage power supply.

If you choose to utilize a third-party power supply unit, you will need to ensure that the power capacity of the power supply is sufficient for the length of LED strip being connected. Use the table below to determine if the power supply is sufficient for your project.

acity

MECHANICAL DRAWING & DIMENSIONS



(This drawing is an excerpt that shows just three complete, cuttable sections. Each reel consists of 200 of these sections).

PART NUMBERS AND ORDERING

4000K: 3001.40 **5000K:** 3001.50

